

HOW TO CHOOSE THE RIGHT PROBE

+44 (0) 1305 265 533
www.cygnus-instruments.com

WHAT ARE YOU TESTING?

CORRODED METALS

THICK
PROTECTIVE
COATING
(UP TO 20MM)

**SINGLE CRYSTAL PROBES
WITH MULTIPLE-ECHO
MEASURING MODE
(PLUS DEEP COAT FUNCTION)**

PROTECTIVE
COATING
(UP TO 3MM)

**SINGLE CRYSTAL PROBES
WITH MULTIPLE-ECHO
MEASURING MODE**

THIN
PROTECTIVE
COATING
(UP TO 1MM)

**SINGLE CRYSTAL PROBES
WITH MULTIPLE-ECHO
MEASURING MODE
(RECOMMENDED)**

OR

**TWIN CRYSTAL PROBES
WITH ECHO-ECHO
MEASURING MODE**

NO
PROTECTIVE
COATING

**SINGLE CRYSTAL PROBES
WITH MULTIPLE-ECHO
MEASURING MODE
(RECOMMENDED)**

OR

**TWIN CRYSTAL PROBES
WITH SINGLE-ECHO
MEASURING MODE**

EXTREMELY CORRODED METALS WITH FRONT OR BACK WALL CORROSION OR PITTING

THIN
PROTECTIVE
COATING
(UP TO 1MM)

**TWIN CRYSTAL PROBES
WITH ECHO-ECHO
MEASURING MODE**

NO
PROTECTIVE
COATING

**TWIN CRYSTAL PROBES
WITH SINGLE-ECHO
MEASURING MODE**

PLASTICS, CAST METALS, COMPOSITES, ATTENUATIVE MATERIALS

NO
PROTECTIVE
COATING

**TWIN CRYSTAL PROBES
WITH SINGLE-ECHO
MEASURING MODE**